

UPS2000-G Series

(1-3kVA)

Introduction

UPS2000-G series with a capacity ranging from 1kVA to 3kVA is an online double conversion power system that delivers continuous, high-quality AC Power. It's really a perfect power protection solution for small power scenarios. It's support tower and rack installation.

Scenarios

- Small and medium-sized enterprises, large enterprise branch offices, bank branches and other small data centers
- Networks, communications systems, automatic control systems and other precision equipment

Features

Reliable

- Wide input voltage range to minimize battery use
- Online double conversion power system provides continuous, high-quality AC Power

Efficient

- Efficiency up to 90%, reduce energy consumption, green and energy-saving
- Ultra small volume, compared to the traditional UPS system to save space

Simple

- LCD screen supports real-time monitoring and convenient operation
- Built-in battery, easy to use
- Enables quick and easy configuration of the UPS
- NetEco network manager, supporting centralized management to all the UPSs



UPS2000-G-1K/2K/3K

Specifications

Rated capacity (kVA/kW)		1kVA/0.8kW	2kVA/1.6kW	3kVA/2.4kW	
Input: Output		1-in: 1-out			
Mains Input	Input Wiring	L+N+PE			
	Rated Voltage	200/208/220/230/240VAC			
	Input Voltage Range	110-300VAC			
	Input Frequency Range	40-70Hz			
	Input Power Factor	0.99			
Bypass Input	Input Rated Voltage	200/208/220/230/240VAC			
	Input Frequency Range	50/60±3Hz			
Battery	Battery Voltage	Standard	24VDC	48VDC	72VDC
		Long Backup	36VDC	72VDC	96VDC
Output	Output Wiring	L+N+PE			
	Output Connections	4 X IEC C13	6 X IEC C13	6 X IEC C13 + 1 X IEC C19	
	Rated Voltage	200/208/220/230/240VAC ±1%			
	Output Frequency	Tracking the bypass input (Normal mode); 50/60Hz ± 0.05%			
	Output Power Factor	0.8			
	Waveform	Sinewave, THDv< 3%			
	System Efficiency	88%	89%	90%	
Environment	Operating Temperature	0 to 40°C			
	Storage Temperature	-40 to +70°C (battery: -20 to +40°C)			
	Relative Humidity	0%–95% RH (no condensation)			
	Operating Altitude	0-1000m. Above 1000m, derating rate based on EN/IEC 62040-3			
	Audible Noise	<50dB			
Others	D x W x H (mm)	Standard	88 x 438 x 310	88 x 438 x 410	88 x 438 x 630
		Long Backup	88 x 438 x 310	88 x 438 x 410	88 x 438 x 410
	Weight (kg)	Standard	11.1	18.8	28.9
		Long Backup	6.0	8.7	9.3
	Certifications	EN/IEC 62040-1; EN/IEC 62040-2; EN/IEC 62040-3; CE; CB; RoHS, REACH, WEEE, etc.			
	Communications	USB&RS232(optional RS485/Dry contact/SNMP)			

Notice:

1. The UPS series are for commercial/industrial use and not used for life support equipment;
2. The critical systems concerning economic and public security must adopt power supply architecture that comply with Uptime TIER III or TIER IV requirements stated in TIA942.